GFX 3.0

Pipe Cutting and Beveling Machine

New, innovative saw from Orbitalum Tools for cutting and beveling of tubes and elbows in just seconds. The perfect preparation for orbital welding!

Easy to use, powerful and compact saw with low weight — our new GFX 3.0 provides even more outstanding features:

Advantages:

- Ideal for press fitting applications
- Square, burr-free and cold machining process
- Deformation-free clamping system especially applicable for thin-walled tubes
- Optimized chip flow due to a new vice design
- Hardened cast iron clamping jaws
- Integrated laser pointer to mark the cut off point
- · Ergonomically designed motor handle
- Powerful drive with 1.2 kW and adjustable speed control for cutting several materials and extended tool life
- Electronic overload protection with integrated temperature monitor and electronic speed regulation
- Ergonomically positioned speed control adjusting wheel
- Swivel cable with a quick-disconnect coupler
- · Second saw blade position to cut off elbows
- Simultaneous or separate cutting and beveling
- · Easy handling through light weight

Your benefits:

- Cost-effective
- Increased productivity
- Long tool life
- Increased durability of tools
- Low-maintenance und service friendly
- · Environmental friendly



Square, burr-free and deformation-free pipe end – ideal for press fitting applications!



Second saw blade position to cut off elbows.



Powerful drive with overload protection and ergonomically designed motor handle.



Hardened cast iron clamping jaws – stainless steel caps optional available.



Integrated laser pointer to mark the cut off point.



Swivel cable with a quick-disconnect coupler.



precision. power. simplicity.

GFX 3.0



Set of stainless steel caps: Ideal for preparing stainless steel tubes.

Prevents contact corrosion between tube and clamping parts. Clamping shells for thin-walled tubes are available on request. Code 790 144 200.



Quick-mounting base plate without screw clamps. Complete with screws and nuts to mount the GFX 3.0 on a work bench. Code 790 041 026.



Code 790 041 027.

Durable storage and shipping case: high-quality padded blue shipping case. Code 790 144 019.

Pipe Cutting and Beveling Machine GFX 3.0

GFX 3.0 (230 V, 50/60 Hz EU) Code 790 144 001								
3.0 (120 V, 50/60 Hz US)			Code 790 144 002					
Application range		Pipe OD minmax.		Saw blade-Ø		Wall thickness minmax		
	[mm]	[inch]	[mm]	[inch]	[mm]	[inch]		
Pipes		0.236 - 3.071	63	2.480	0.8 - 5.5	0.032 - 0.217		
		0.236 - 2.874	68	2.677	0.8 - 7.0	0.032 - 0.276		
Bars		0.236 - 0.630	63	2.480	-	-		
		0.236 - 0.827	68	2.677	-	-		
Pipe Materials			Unalloyed steel, low alloy steel, high alloy steel, stainless steel, nonferrous metal, aluminum alloy, titanium alloy, composite material and plastic.					
Technical data Electri			ectric drive with single-phase AC motor					
Dimensions (lxhxd) [mm]			570 x 280 x 330					
[inch]	22.441 x 11.024 x 12.993							
Weight (without clamping shells) [kg]			28.1					
[lbs]	62.04							
	II .							
[V, Hz]	230 V, 50/60 Hz EU or 120 V, 50/60 Hz US							
[W]	1200							
[rpm]	30 - 200							
$[m/s^2]$	< 2.5							
	[inch] [kg] [lbs] [V, Hz] [W] [rpm]	Code 790 144 0 Pipe OD [mm] 6.0 - 78.0 6.0 - 73.0 6.0 - 16.0 6.0 - 21.0 Unalloyed steel alloy, titanium Electric drive [mm] 570 x 280 x 330 [inch] 22.441 x 11.024 [kg] 28.1 [lbs] 62.04 I [V, Hz] 230 V, 50/60 Hz [W] 1200 [rpm] 30 - 200	Code 790 144 002 Pipe OD minmax.	Pipe OD minmax. Saw black [mm] [inch] [mm] [inch] [mm]	Code 790 144 002 Pipe OD minmax. Saw blade-Ø	Code 790 144 002 Pipe OD minmax. Saw blade-Ø Wall thicknee [mm] [inch] [mm] [inch] [mm]		

1 Pipe Cutting and Beveling Machine GFX 3.0 • 1 Transportation case • 1 Saw blade (Code 790 048 072) • 1 Tool set • 1 Tube of saw blade lubricant GFTOP (Code 790 060 228) • 1 Set of operating instructions and spare parts list

The technical data is non-binding. It does not include any assurance of properties. Subject to change. Our general terms and conditions apply.

© Orbitalum Tools GmbH (10.2010)



Orbitalum Tools GmbH, Josef-Schuettler-Str. 17, 78224 Singen, Germany

Sales Contact:

Stamp of distributor:

Tel. +49 (0) 77 31 792-786 up to -789 Fax +49 (0) 77 31 792-524 tools@orbitalum.com www.orbitalum.com

Repair Service:

Josef-Schuettler-Str. 17 78224 Singen, Germany Tel. +49 (0) 77 31 792-764 Fax +49 (0) 77 31 792-524